



Underfloor Heat Pump



Superior Climate Control

Safe

Quiet

No draughts

Heats and cools

Very cost effective to run

No condensation created

A healthy way to heat



Selected by OASIS
26 years of experience
is your guarantee of quality

A purpose built complete package
2 year on site parts and labour
(metro area)

The best you can buy
Top quality manufacturing
Uses the latest technology
and green refrigerant
Designed for the job
No Legionella bacteria
Soft Start system
Extensive supplier network

OASIS UNDERFLOOR HEAT PUMP

Superior Climate Control



Oasis 080B-U

Model	Oasis	020B	030B	040B	050B	060B-U	080B-U
Heating output	Kw	5.5	8.1	10.5	12.5	17	21
Heating power input	Kw	1.8	2.85	3.7	4.3	6.3	7.4
Max power input	Kw	2.2	3.4	4.4	5.2	7.56	8.9
Power supply	V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	380/3/50
Soft start		Yes	Yes	Yes	Yes	Yes	Yes
Running current	Amps	8.2	13	16	19.5	28.3	15.6
Compressor type		rotary	rotary	Scroll	Scroll	rotary	Scroll
Fan quantity		1	1	2	2	2	2
Noise level	dB[A]	54	56	59	59	61	61
Air discharge		Horizontal	Horizontal	Horizontal	Horizontal	Vertical	Vertical
Water pump make		Wilo	Grundfos	Wilo	Wilo	Wilo	Wilo
Water flow volume	L/S	0.25	0.36	0.47	0.64	0.9	1.1
Water pump pressure	M	6	8	10	10	20	20
Water pressure drop	kPa	17	29	31	32.5	35	40
Water connection	mm	19	25	25	25	38	38
Water storage capacity	L	15	23	32	32	60	60
Refrigerant		R407C	R407C	R407C	R407C	R407C	R407C
Heat exchanger type		Plate	Plate	Plate	Plate	Plate	Plate
Unit dimensions L/W/H	mm	1115*470*650	1115*470*850	1115*470*1245	1115*470*1245	1450*730*1080	1450*730*1080
Unit net weight	Kg	90	120	140	150	280	300

Condition: heating - outdoor air temp. 7 °C/6 °C, outlet water temp. 45 °C, inlet water temp. 40 °C.

Your Supplier:

www.hotwater.co.nz
info@hotwater.co.nz

