

Specifications



www.oasisheatpumps.com

MODEL	Oasis	C12A	C17A	C21A
Heating Capacity*	KW	12.0	14.4	19.0
	BTU/h	41000	50000	65000
Heating Capacity**	KW	13.0	16.0	21.0
	BTU/h	45000	55000	72000
Compressor	Type	Rotary	Scroll	Scroll
	Quantity	1	1	1
Heating Power Input*	KW	2.5	3.1	4.2
Heating Power Input**	KW	2.5	3.1	4.2
Power Supply	V/PH/Hz	220/1/50	220/1/50	380/3/50
Fan Quantity		1	1	1
Fan Power Input (Vertical / Side)	W	220/120	220/120	200
Fan Speed (Vertical / Side)	Rpm	670/850	670/850	670
Water Flow Volume	m ³ /h	3~4.5	6	5~7.5
Water Pressure Drop	KPa	12	10	8
Noise	dB(A)	54	54	57
Water Connection	Inch	2	2	2
Net Weight	KG	80	90	119
Net Dimensions(L/W/H)	mm	1110/440/700	1110/440/700	1110/440/1360

MODEL	Oasis	C25A	C50A
Heating Capacity*	KW	23.0	47.0
	BTU/h	81000	162000
Heating Capacity**	KW	26.0	52.0
	BTU/h	90000	180000
Compressor	Type	Scroll	Scroll
	Quantity	1	2
Heating Power Input*	KW	5.1	5.1*2
Heating Power Input**	KW	5.1	5.1*2
Power Supply	V/PH/Hz	380/3/50	380/3/50
Fan Quantity		1	2
Fan Power Input (Vertical / Side)	W	250	250
Fan Speed (Vertical / Side)	Rpm	670	670
Water Flow Volume	m ³ /h	8	18
Water Pressure Drop	KPa	10	12
Noise	dB(A)	57	59
Water Connection	Inch	2	3
Net Weight	KG	128	325
Net Dimensions(L/W/H)	mm	1110/440/1360	1500/850/1300

Measurement Conditions:

* Heating Outdoor Air Temp. : 15°C / 11°C , Water Inlet Temp. : 27°C

* Heating Outdoor Air Temp. : 24°C / 19°C , Water Inlet Temp. : 27°C